


# SECTION

DO NOT SCALE

## Notes



This detail shows a method of draining water through an abutting intermediate slab so that it can be received by the the Newton Waterproofing System at the lowest level of the basement. It requires that a recess be formed with an engineering brick to act as a drainage channel. The recess is drained by 40mm I/D plastic pipes at 5m centres. Water draining via the pipes is collected by a coving detail of Newton 508 Wall membrane.

There should be a minimum of two pipe penetrations on every run.

The recess should be coated with Newton 107F waterproof coating so that dampness cannot migrate from the recess to the slab. The membrane should be reinforced at the change in direction from horizontal to vertical with Newton 912-RT as recommended within the product data sheet.

Use in conjunction with a Newton CDM System drawing prefixed CDM that will show the detailing at the lower raft/slab level.

A) Newton HydroCoat 104 Super is applied to the surface of the wall prior to the placement of the slab to prevent moisture transmitting to the slab from the wall by capillary. Not applicable for remedial installation of the waterproofing. Not required if capillary blocking additive is added to the concrete prior to placement.

B) i) Newton DampSafe 809-HP DPC is taped to Newton Floor Membrane with Newton CDM WaterSeal Tape - not shown.

ii)Take the Newton DampSafe 809-HP DPC across onto the top of the BaseDrain within the cavity as shown - (option).

To access further details and relevant technical information please call our Technical Team on 01732 360 095 or refer to our [website](#).

NOTE: This is a Newton waterproofing detail and copyright remains with John Newton & Co. Ltd. (trading as Newton Waterproofing Systems). Any specification/advice provided is only valid if used with products supplied by John Newton & Co. Ltd. For the design of the structure, please use a professional designer. We recommend that Newtons' waterproofing systems are installed by our NSBC registered contractors who can offer insurance backed guarantees and accept liability for both the design and installation of our systems. Please refer to product data sheets before installation of our products.

Newton Waterproofing Systems reserve the right to update drawings and product literature at any time.



© Newton Waterproofing Systems  
(a trading name of John Newton & Co. Ltd.)  
Newton House, 17 - 20 Sovereign Way, Tonbridge, Kent, TN9 1RH, T: 01732 360 095  
Unit 6b, Gibraltar Island Road, Old Mill Business Park, Leeds, LS10 1RJ, T: 0113 521 6777  
W: [www.newtonwaterproofing.co.uk](http://www.newtonwaterproofing.co.uk) E: [tech@newtonwaterproofing.co.uk](mailto:tech@newtonwaterproofing.co.uk)

Newton CDM System  
Pipe through intermediate slab to allow  
draining of the Newton CDM System to  
lower level

Reference	JN-CDM-D19A	Designed	DGB
Revision	e	Drawn	AJG
Date	22/11/2024	Checked	