# DampSafe 802

# Damp Proof Membrane



Revision: 1.5 - 1st December 2022 Code: 802

## 1. Product and Company identification

#### **Product Identifier**

Identification of Substances or Preparation: Low density re-cycled Polyethylene.

Company Identification: Newton Waterproofing Systems, Newton House, 17-20 Sovereign Way,

Tonbridge, Kent TN9 1RH

Web www.newtonwaterproofing.co.uk

Email address of the competent person

info@newtonwaterproofing.co.uk

Emergency telephone number +44 (0)1732 360 095: 08:00/17:30 (GMT) Mon-Thur & 08:00/17:00 (GMT) Fri

#### 2. Composition/information on ingredients

100% re-cycled Low density Polyethylene (coloured Products include a maximum of 3% pigment)

Other additives may be included to achieve special properties depending on the end use of the product.

Coloured Sheeting will include a maximum of 3% Carbon Pigment.

There is no toxic element incorporated in the finished material and does not normally constitute a hazard.

#### 3. Hazard Identification (Directive 67/548/EEC

None

#### 4. First Aid Measures

a. Skin Contact No Special Measures

b. Eye Contact "

c. Inhalation "

d. Ingestion

# SECTION 5. Fire-Fighting Measures

a. Suitable Extinguishing Media: Dry Powder

b. Unsuitable Extinguishing Media Water. Advice can be sought from local Fire authority

c. Exposure Hazards Gasses will be given off in a major fire situation, consult your local

Fire authority.

e. Protective Equipment for Fire Fighters

Use self-contained breathing apparatus.

# DampSafe 802

# Damp Proof Membrane

#### 6. Accidental Release Measures

a. Personal Precautionsb. Environmental PrecautionsNone

c. Method of Cleaning up: Not Applicable

#### **SECTION 7. Handling and Storage**

a. Precautions during handling

There are no special precautions recommended for safe handling of flexible

Polythene sheeting

b. Storage If significant quantities of Polythene sheeting are stored, the local fire

authorities should be advised of the fact in order that they are forewarned

of the possible hazard.

### 8. Exposure Controls / Personal Protection

a. Exposure Control Limits Noneb. Special Protective Measures None

### 9. Physical and Chemical Properties

a. Physical State Sheet Material

b. Odour Faint

c. Decomposition Temperature Begins at 160 degrees Cent. Decomposition is a function of time, high

processing temperatures should not be applied for long periods. Above 200

degrees Cent decomposition occurs rapidly.

d. Flammability will burn if it comes into direct contact with a naked flame or a radiant heat

source such infrared heating element.

#### SECTION 10. Stability and Reactivity

a. Thermal Decomposition Decomposition will start at 160 degrees Cent.

b. Conditions to avoidc. Materials to AvoidNone

## **SECTION 11. Toxicological Information**

a. Residual Monomer When heated the sheeting do not depolymerise

b. Toxic Ingredients. Does not constitute a toxic hazard. However, being made of totally recycled

product it should not be used for directly wrapping food nor should sheet be used for children's playthings unless specifically formulated for this

purpose.

# SECTION 12. Ecological Information

a. Environmental Effect: The product is not biologically decomposable. It degrades under prolonged

ultraviolet exposure. It floats on water and is insoluble in water. No

bioaccumulation known. The product is non toxic.

# DampSafe 802

# Damp Proof Membrane

#### **SECTION 13. Disposal Considerations**

a. Disposal of Product Through normal trade re-cycling outlets

b. Disposal of Packaging

By re-cycling. We are an accredited Re-cycler with the Department of the Environment and can take all LDPE products back for re-cycling and re-use.

#### SECTION 14. Transport Information

a. No Special Precautions required

b. ADR Nonec. UN Number None

### SECTION 15. Regulatory Information

a. Risk Phraseb. Safety Phrasec. Classification SymbolNone

#### SECTION 16. Other Information

a. Uses Various

b. Processing Involving Heat In operations such as HF Weldingor Vacuum Forming etc., excessive heat may give

rise to evolution of plasticiser fumes, none of which are harmful or toxic.

c. Static Electricity Build up of static electricity in rolls of Polythene film and sheeting may cause

sparking when the material is earthed. In areas where this may be a potential hazard e.g. near flammable solvents, steps should be taken to eliminate safely the static charge and to prevent or minimise Subsequent recharging during further processing.

d. REACH The data contained in this Material Safety Data Sheet has been prepared in

accordance with formatting described in the REACH Regulation (EC) No 1907/2006, and described in CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures for the purpose of protecting the health and safety of industrial and commercial users who are deemed capable of and acting on the information provided. Please ensure that it is passed to the appropriate

person(s) in your company, who capable of acting on the information.