

# DampSafe 802-DPM

1200 Gauge Damp Proof Membrane

Revision: 1.5 - 1st December 2022  
Code: 802-DPM



EN 13967:2012

## DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) No. 305/2011

### 1. UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE

802-DPM

### 2. IDENTIFICATION AND USE

DampSafe 802-DPM is a 300 micron flexible sheet for waterproofing

### 3. INTENDED USE OF DAMPSAFE 802-DPM PRODUCTS

For use in solid concrete ground floors that are not subject to hydraulic pressure to protect buildings against water from the ground

### 4. MANUFACTURER

Newton Waterproofing Systems  
(a trading name of John Newton & Company Ltd.)  
Newton House  
17-20 Sovereign Way  
Tonbridge  
Kent  
TN9 1RH  
01732 360095  
[www.newtonwaterproofing.co.uk](http://www.newtonwaterproofing.co.uk)

### 5. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE

System 2+

### 6. THE NOTIFICATION FACTORY CONTROL CERTIFICATION BODY IS BBA, BRITISH BOARD OF AGREEMENT

The BBA performed inspection of manufacturing plant and factory control and carried out continuous surveillance, assessment and evaluation of factory production control under system 2+ as described in harmonized standard EN 13967.

# DampSafe 802-DPM

## 1200 Gauge Damp Proof Membrane

### 7. TECHNICAL SPECIFICATIONS

#### 7.1 Description

DampSafe 802 Damp-proof membranes are a blown film of extruded polythene

Nominal spec.		Tolerance %
Thickness- micron	300	+/- 10% (-0% 400mic)
Roll length mts	25	-0/ + 5%
Roll width mts	4	-0/5%
Colours- blue/ black/ yellow/clear.		

#### TEST. EN13967.

	300MU
TENSILE-EN12311:2	125MLV
THICKNESS -EN1849-2	+/-10%
DROP DART-EN12691	30MLV
WIDTH - EN1848-2	4MT
NAIL TARE-EN12310	130MLV

#### BBA TESTING.

STATIC LOAD EN 12730	ALL PASS @ 20KGS METHOD B.
WATER PERMEABILITY-EN1931	PASS
WATER TIGHTNESS-EN1928	*CONTROL- PASS
	*CHEMICAL- PASS
	*HEAT AGED- PASS

### 8. DECLARATION

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Name: Warren Muschialli - Managing Director



At: Newton Waterproofing Systems  
Newton House, 17-20 Sovereign Way  
Tonbridge, Kent, TN9 1RH

On: 2nd December 2022



# DampSafe 802-DPM

1200 Gauge Damp Proof Membrane

	 <p>Newton Waterproofing Systems Newton House 17-20 Sovereign Way Tonbridge Kent TN9 1RH</p>	<p>401M BS EN 13967 1213 300 micron flexible sheet for waterproofing</p>												
<table><tr><td>TENSILE-EN12311:2</td><td>300MU</td></tr><tr><td>THICKNESS -EN1849-2</td><td>125MLV</td></tr><tr><td>DROP DART-EN12691</td><td>+/-10%</td></tr><tr><td>WIDTH - EN1848-2</td><td>30MLV</td></tr><tr><td>NAIL TARE-EN12310</td><td>4MT</td></tr><tr><td></td><td>130MLV</td></tr></table>			TENSILE-EN12311:2	300MU	THICKNESS -EN1849-2	125MLV	DROP DART-EN12691	+/-10%	WIDTH - EN1848-2	30MLV	NAIL TARE-EN12310	4MT		130MLV
TENSILE-EN12311:2	300MU													
THICKNESS -EN1849-2	125MLV													
DROP DART-EN12691	+/-10%													
WIDTH - EN1848-2	30MLV													
NAIL TARE-EN12310	4MT													
	130MLV													
<p><b>BBA TESTING.</b></p> <table><tr><td>STATIC LOAD EN 12730</td><td>ALL PASS @ 20KGS METHOD B.</td></tr><tr><td>WATER PERMEABILITY-EN1931</td><td>PASS</td></tr><tr><td>WATER TIGHTNESS-EN1928</td><td>*CONTROL- PASS</td></tr><tr><td></td><td>*CHEMICAL- PASS</td></tr><tr><td></td><td>*HEAT AGED- PASS</td></tr></table>			STATIC LOAD EN 12730	ALL PASS @ 20KGS METHOD B.	WATER PERMEABILITY-EN1931	PASS	WATER TIGHTNESS-EN1928	*CONTROL- PASS		*CHEMICAL- PASS		*HEAT AGED- PASS		
STATIC LOAD EN 12730	ALL PASS @ 20KGS METHOD B.													
WATER PERMEABILITY-EN1931	PASS													
WATER TIGHTNESS-EN1928	*CONTROL- PASS													
	*CHEMICAL- PASS													
	*HEAT AGED- PASS													