

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

Revision: 3.0 - 13th October 2026

Code: 107F

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Identifier

- Product form Mixture
- Product name HydroCoat 107 Elastic 2K
- Product codes 107F

Relevant identified uses of the substance and uses advised against

- Use of substance/mixture Professional use Industrial use
- Uses advised against All Other Uses
- Product use Cementitious Coating

Details of the Supplier of the Safety Data Sheet

- Company Address Newton Waterproofing Systems, Newton House, 17-19 Sovereign Way, Tonbridge, Kent TN9 1RH
- Web www.newtonwaterproofing.co.uk
- Email address of the competent person info@newtonwaterproofing.co.uk
- Emergency telephone numbers Newton Waterproofing systems - English language
+44 (0)1732 360095/08:00-17:30 (GMT) Mon-Thur & 08:00-17:00 (GMT) Fri

Emergency telephone number

National advisory body/Poison Center

- Telephone number +44 (0)344 892 0111

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label Elements

Hazard pictograms



- Signal words Warning
- Hazard statements H317 - May cause an allergic skin reaction.

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

Precautionary statements

Prevention	P280 - Wear protective gloves. P261 - Avoid breathing vapor.
Response	P362 + P364 - Take off contaminated clothing and wash it before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. Storage
Storage	Not applicable.
Disposal	P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations.
Hazardous ingredients	1,2-benzisothiazol-3(2H)-one CMIT/MIT(3:1)

Supplemental label elements Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Special packaging requirements

Containers to be fitted with child-resistant fastenings Not applicable.

Tactile warning of danger Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No.1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Type
1,2-benzisothiazol-3(2H)- one	REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5	<0.1	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 450 mg/kg ATE [Inhalation (dusts and mists)] = 0.21 mg/l Skin Sens. 1, H317: C ≥ 0.036% M [Acute] = 1	[1]
CMIT/MIT(3:1)	REACH #: 01-2120764691-48 EC: 911-418-6 CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 EUH071 See Section 16 for the full text of the H statements declared above.	M [Chronic] = 1 ATE [Oral] = 100 mg/kg ATE [Dermal] = 50 mg/kg ATE [Inhalation (dusts and mists)] = 0.05 mg/l Skin Corr. 1C, H314: C ≥ 0.6% Skin Irrit. 2, H315: 0.06% ≤ C < 0.6% Eye Dam. 1, H318: C ≥ 0.6% Eye Irrit. 2, H319: 0.06% ≤ C < 0.6% Skin Sens. 1, H317: C ≥ 0.0015% M [Acute] = 100 M [Chronic] = 100	[1]

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

^[1] Substance classified with a physical, health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

4. FIRST AID MEASURES

4.1 Description of First Aid Measures

- **Eye contact** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- **Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- **Skin contact** Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- **Ingestion** Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- **Protection of first-aiders** No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Over-exposure signs / symptoms:

- **Eye contact** No specific data.
- **Inhalation** No specific data.
- **Skin contact** Adverse symptoms may include the following: irritation
redness
- **Ingestion** No specific data.

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

- **Notes to physician** Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- **Specific treatments** No specific treatment.

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

Suitable extinguishing media	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	No specific data.

5.3 Advice for Firefighters

Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

- For non-emergency personnel
No action shall be taken involving any personal risk or without suitable training.
Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders
If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental Precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and Materials for Containment and Cleaning Up

- Small spill
Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill
Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to Other Sections

See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

7. HANDLING AND STORAGE

The information in this section contains generic advice and guidance.

7.1 Precautions for Safe Handling

- Protective measures Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for Safe Storage, Including Any Incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific End Use(es)

- Recommendations Not available.
- Industrial sector specific solutions Not available.

8. PERSONAL PROTECTION/EXPOSURE CONTROL

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control Parameters

Occupational exposure limits No exposure limit value known.

Recommended monitoring procedures If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

DNELs / DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
1,2-benzisothiazol-3(2H)-one CMIT/MIT(3:1)	DNEL	Long term Dermal	0.345 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.966 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	6.81 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	0.02 mg/m ³	General population	Local
	DNEL	Long term Inhalation	0.02 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	0.04 mg/m ³	General population	Local
	DNEL	Short term Inhalation	0.04 mg/m ³	Workers	Local
	DNEL	Long term Oral	0.09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.11 mg/ kg bw/day	General population	Systemic

PNECs

No PNECs available

8.2 Exposure Controls

- Appropriate Engineering Controls Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

- Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

- Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness ≥ 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

- Body protection

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
- Other skin protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Wear a respirator conforming to EN140 with type A/P2 filter or better. Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.
- Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on Basic Physical and Chemical Properties

Appearance

- Physical state Liquid
- Colour White.
- Odour Characteristic.
- Odour threshold Not available.
- Melting point/freezing point Not available.
- Boiling point, initial boiling point, and boiling range 100°C (212°F)
- Flammability Not available.
- Lower and upper explosion limit Not available.
- Flash point Not available.
- Auto-ignition temperature Not available.
- Decomposition temperature Not available.
- pH 6.9 [Conc. (% w/w): 0%] [DIN EN 1262]
- Viscosity Kinematic (room temperature): 2325 mm²/s [DIN EN ISO 3219]
Kinematic (40°C): 2413 mm²/s [DIN EN ISO 3219]
- Solubility(ies)

Media	Result
cold water	Soluble [OECD (TG 105)]

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

- Partition coefficient: n-octanol/water Not applicable.
- Vapor pressure Not applicable.
- Density 1.038 g/cm³ [DIN EN ISO 2811-1]
- Vapor density Not applicable.

Particle characteristics

- Median particle size Not available.
- Percentage of particles with aerodynamic diameter ≤ 10 µm 0
- Minimum ignition energy (mJ) Not available.
- Fundamental burning velocity Not applicable.
- SADT Not available.
- Heat of combustion Not available.

Aerosol product

- Type of aerosol Not applicable.

10. STABILITY AND REACTIVITY

- 10.1 Reactivity** No specific test data related to reactivity available for this product or its ingredients
- 10.2 Chemical Stability** The product is stable.
- 10.3 Possibility of Hazardous Reactions** Under normal conditions of storage and use, hazardous reactions will not occur
- 10.4 Conditions to Avoid** No specific data
- 10.5 Incompatible Materials** No specific data
- 10.6 Hazardous Decomposition Products** Under normal conditions of storage and use, hazardous decomposition products should not be produced

11. TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-benzisothiazol-3(2H)-one	LD50 Oral	Mouse	1150 mg/kg	-
	LD50 Oral	Rat	1020 mg/kg	-

- Conclusion/Summary : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0.21
CMIT/MIT(3:1)	100	50	N/A	N/A	0.05

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

Irritation / Corrosion

- Conclusion/Summary : Not available.

Sensitisation

- Conclusion/Summary : Not available.

Mutagenicity

- Conclusion/Summary : Not available.

Carcinogenicity

- Conclusion/Summary : Not available.

Reproductive toxicity

- Conclusion/Summary : Not available.

Teratogenicity

- Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

- Not available.

Specific target organ toxicity (repeated exposure)

- Not available.

Aspiration hazard

- Not available.

Information on likely routes of exposure

- Not available.

Potential acute health effects

- | | |
|----------------|---|
| • Eye contact | No known significant effects or critical hazards. |
| • Inhalation | No known significant effects or critical hazards. |
| • Skin contact | May cause an allergic skin reaction. |
| • Ingestion | No known significant effects or critical hazards. |

Symptoms related to the physical, chemical and toxicological characteristics

- | | |
|----------------|---|
| • Eye contact | No specific data. |
| • Inhalation | No specific data. |
| • Skin contact | Adverse symptoms may include the following: irritation
redness |
| • Ingestion | No specific data. |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short-term exposure

- | | |
|-------------------------------|----------------|
| • Potential immediate effects | Not available. |
| • Potential delayed effects | Not available. |

Long-term exposure

- | | |
|-------------------------------|----------------|
| • Potential immediate effects | Not available. |
| • Potential delayed effects | Not available. |

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

Potential chronic health effects

- Not available.
- Conclusion/Summary Not available.
- General Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
 - Carcinogenicity No known significant effects of critical hazards
 - Mutagenicity No known significant effects of critical hazards
 - Reproductive toxicity No known significant effects of critical hazards

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

No additional information.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

There are no data available on the mixture itself.

Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment, but contains substance(s) hazardous to the environment. See section 3 for details.

Product/ingredient name	Result	Species	Exposure
1,2-benzisothiazol-3(2H)-one	Acute EC50 97 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2.24 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 3.7 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 1.1 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute EC50 2 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 10 to 20 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
			96 hours
	Acute LC50 540 ppb Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 167 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 0.75 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 1.6 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

- Conclusion / Summary Not available.

12.2 Persistence and Biodegradability

- Conclusion / Summary Not available.

12.3 Bioaccumulative Potential

- Not available.

12.4 Mobility in Soil

- Soil/water partition coefficient (K_{oc}) Not available.
- Mobility Not available.

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

12.5 Results of PBT & vPvT Assessment

- This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

- Not available.

12.7 Other Adverse Effects

- No known significant effects or critical hazards

13. DISPOSAL CONSIDERATIONS

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste Treatment Methods

Product

Methods of disposal

The generation of waste should be avoided or minimized wherever possible.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

The classification of the product may meet the criteria for a hazardous waste.

Disposal considerations

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 12	waste paint and varnish other than those mentioned in 08 01 11

Packaging

- Methods of disposal:

The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

- Disposal considerations

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

- Special precautions :

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

14. TRANSPORT INFORMATION

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

- 14.6 Special Precautions for User** Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
- 14.7 Transport in Bulk According to to IMO instruments** Not applicable.

15. REGULATORY INFORMATION

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance, Mixture

UK (GB) /REACH

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles: Not applicable.

Other EU regulations

VOC : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : Not available.

Industrial emissions (integrated pollution prevention and control) - Air :

Not listed

Industrial emissions (integrated pollution prevention and control) - Water :

Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

National regulations

Biocidal products regulation

Active substances

Ingredient name
formaldehyde CMIT/MIT(3:1)

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical Safety Assessment No Chemical Safety Assessment has been carried out.

16. OTHER INFORMATION

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

Full text of abbreviated H statements

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Full text of classifications [CLP/GHS]

Acute Tox. 2	ACUTE TOXICITY - Category 2
Acute Tox. 3	ACUTE TOXICITY - Category 3
Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1	AQUATIC HAZARD (LONG-TERM) - Category 1
Carc. 1B	CARCINOGENICITY - Category 1B
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Muta. 2	GERM CELL MUTAGENICITY - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Corr. 1C	SKIN CORROSION/IRRITATION - Category 1C
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1A	SKIN SENSITIZATION - Category 1A
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3

Date of printing : 10-7-2025
Date of issue/ Date of revision : 10-7-2025
Date of previous issue : 7-11-2024
Version: 2
Unique ID : BB61C204F4D31EEFA7A40AC59BC8C747

HydroCoat 107 Elastic 2K Part A

Cementitious Flexible Waterproofing Membrane

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws; any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Please make sure to refer to these and / or the relevant agreement which you have with Newton Waterproofing Systems.

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

Revision: 3.0 - 13th October 2026

Code: 107F

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Identifier

- Product form Mixture
- Product name HydroCoat 107 Elastic 2K
- Product codes 107F

Relevant identified uses of the substance and uses advised against

- Use of substance/mixture Professional use Industrial use
- Uses advised against All Other Uses
- Product use Cementitious Coating

Details of the Supplier of the Safety Data Sheet

- Company Address Newton Waterproofing Systems, Newton House, 17-19 Sovereign Way, Tonbridge, Kent TN9 1RH
- Web www.newtonwaterproofing.co.uk
- Email address of the competent person info@newtonwaterproofing.co.uk
- Emergency telephone numbers Newton Waterproofing systems - English language
+44 (0)1732 360095/08:00-17:30 (GMT) Mon-Thur & 08:00-17:00 (GMT) Fri

Emergency telephone number

National advisory body/Poison Center

- Telephone number +44 (0)344 892 0111

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label Elements

- Signal words No signal word.
- Hazard statements No known significant effects or critical hazards.

Precautionary statements

- General Not applicable.
- Prevention Not applicable.
- Response Not applicable.
- Storage Not applicable.
- Disposal Not applicable.
- Supplemental label elements Not applicable.

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

Not applicable.

Tactile warning of danger

Not applicable.

2.3 Other Hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

None known

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Other Hazards

- Mixtures : Mixture

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

4. FIRST AID MEASURES

4.1 Description of First Aid Measures

- Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses if easy to do. Get medical attention if irritation occurs.
- Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
- Skin contact Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
- Protection of first-aiders No action shall be taken involving any personal risk or without suitable training.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Over-exposure signs / symptoms:

- Eye contact No specific data.
- Inhalation No specific data.
- Skin contact No specific data.
- Ingestion No specific data.

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

- Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments No specific treatment.

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

Suitable extinguishing media	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	No specific fire or explosion hazard
Hazardous combustion products	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide / oxide

5.3 Advice for Firefighters

Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

- For non-emergency personnel
No action shall be taken involving any personal risk or without suitable training.
Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
- For emergency responders
If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental Precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and Materials for Containment and Cleaning Up

- Small spill
Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.
- Large spill
Move containers from spill area. Prevent entry into sewers, water courses basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.

6.4 Reference to Other Sections

See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

7. HANDLING AND STORAGE

The information in this section contains generic advice and guidance.

7.1 Precautions for Safe Handling

- Protective measures Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for Safe Storage, Including Any Incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific End Use(es)

- Recommendations Not available.
- Industrial sector specific solutions Not available.

8. PERSONAL PROTECTION/EXPOSURE CONTROL

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control Parameters

Occupational exposure limits

Recommended monitoring procedures:

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs / DMELs

No DNELs / DMELs available

PNECs

No PNECs available

8.2 Exposure Controls

- Appropriate Engineering Controls Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

- Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing.

Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

- Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields

Skin protection

- Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

For all types of exposure, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness ≥ 0.12 mm.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

- Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

- Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used. Wear a Approved/certified disposable particulate dust mask.

- Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels

9. PHYSICAL AND CHEMICAL PROPERTIES

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on Basic Physical and Chemical Properties

Appearance

- | | |
|--------------------------------|----------------|
| • Physical state | Solid. |
| • Colour | Grey. |
| • Odour | Odourless. |
| • Odour threshold | Not available. |
| • Melting point/freezing point | Not available. |

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

- Boiling point, initial boiling point, and boiling range Not applicable.
- Flammability Not available.
- Flash point Not applicable.
- Auto-ignition temperature Not applicable.
- Decomposition temperature Not available.
- pH Not applicable. [DIN EN 1262]
- Viscosity Kinematic (room temperature): Not applicable. [DIN EN ISO 3219]
Kinematic (40°C): Not applicable. [DIN EN ISO 3219]
- Solubility(ies)

Media	Result
cold water	Soluble [OECD (TG 105)]

- Partition coefficient: n-octanol/water Not applicable.
- Vapor pressure Not applicable.
- Density 2.719 g/cm³ [DIN EN ISO 2811-1]
- Vapor density Not applicable.

Particle characteristics

- Median particle size Not available.
- Percentage of particles with aerodynamic diameter ≤ 10 µm 0
- Minimum ignition energy (mJ) Not available.
- Fundamental burning velocity Not applicable.
- SADT Not available.
- Heat of combustion Not available.

Aerosol product

- Type of aerosol Not applicable.

10. STABILITY AND REACTIVITY

- 10.1 Reactivity** No specific test data related to reactivity available for this product or its ingredients
- 10.2 Chemical Stability** The product is stable.
- 10.3 Possibility of Hazardous Reactions** Under normal conditions of storage and use, hazardous reactions will not occur
- 10.4 Conditions to Avoid** No specific data
- 10.5 Incompatible Materials** No specific data
- 10.6 Hazardous Decomposition Products** Under normal conditions of storage and use, hazardous decomposition products should not be produced

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

11. TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Acute toxicity

- Conclusion/Summary : Not available.
- Acute toxicity estimates : N/A

Irritation / Corrosion

- Conclusion/Summary : Not available.

Sensitisation

- Conclusion/Summary : Not available.

Mutagenicity

- Conclusion/Summary : Not available.

Carcinogenicity

- Conclusion/Summary : Not available.

Reproductive toxicity

- Conclusion/Summary : Not available.

Teratogenicity

- Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

- Not available.

Specific target organ toxicity (repeated exposure)

- Not available.

Aspiration hazard

- Not available.

Information on likely routes of exposure

- Not available.

Potential acute health effects

- | | |
|----------------|---|
| • Eye contact | No known significant effects or critical hazards. |
| • Inhalation | No known significant effects or critical hazards. |
| • Skin contact | No known significant effects or critical hazards. |
| • Ingestion | No known significant effects or critical hazards. |

Symptoms related to the physical, chemical and toxicological characteristics

- | | |
|----------------|-------------------|
| • Eye contact | No specific data. |
| • Inhalation | No specific data. |
| • Skin contact | No specific data. |
| • Ingestion | No specific data. |

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short-term exposure

- Potential immediate effects Not available.
- Potential delayed effects Not available.

Long-term exposure

- Potential immediate effects Not available.
- Potential delayed effects Not available.

Potential chronic health effects

- Not available.

Conclusion/Summary Not available.

- General No known significant effects of critical hazards
- Carcinogenicity No known significant effects of critical hazards
- Mutagenicity No known significant effects of critical hazards
- Reproductive toxicity No known significant effects of critical hazards

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

No additional information.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

- There are no data available on the mixture itself. Do not allow to enter drains or watercourses. The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

12.2 Persistence and Biodegradability

- Conclusion / Summary Not available.

12.3 Bioaccumulative Potential

- Not available.

12.4 Mobility in Soil

- Soil/water partition coefficient (K_{oc}) Not available.
- Mobility Not available.

12.5 Results of PBT & vPvT Assessment

- This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

- Not available.

12.7 Other Adverse Effects

- No known significant effects or critical hazards

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

13. DISPOSAL CONSIDERATIONS

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste Treatment Methods

Product

- Methods of disposal
The generation of waste should be avoided or minimized wherever possible.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Hazardous waste
Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.
- Disposal considerations
Do not allow to enter drains or watercourses.
Dispose of according to all federal, state and local applicable regulations.
If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned
For further information, contact your local waste authority.

European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
EWC 08 01 99	wastes not otherwise specified

Packaging

- Methods of disposal:
The generation of waste should be avoided or minimized wherever possible.
Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Disposal considerations
Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned
Dispose of containers contaminated by the product in accordance with local or national legal provisions.
- Special precautions :
This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	-

14.6 Special Precautions for User

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

14.7 Transport in Bulk According to IMO instruments Not available.

15. REGULATORY INFORMATION

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance, Mixture

UK (GB) /REACH

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

Other EU regulations

VOC The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

VOC for Ready-for-Use Mixture : Not available.

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Biocidal products regulation

Active substances

Ingredient name
citric acid
glyoxal

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

HydroCoat 107 Elastic 2K Part B

Cementitious Flexible Waterproofing Membrane

Rotterdam Convention on Prior Informed Consent (PIC)
Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals
Not listed.

15.2 Chemical Safety Assessment No Chemical Safety Assessment has been carried out.

16. OTHER INFORMATION

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
N/A = Not available
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
SGG = Segregation Group
vPvB = Very Persistent and Very Bioaccumulative

Classification	Justification
Not classified.	

Full text of abbreviated H statements Not applicable.

Full text of classifications [CLP/GHS] Not applicable.

Date of printing : 13-2-2025

Date of issue/ Date of revision : 13-2-2025

Date of previous issue : No previous validation

Version : 1

Unique ID : BB61C204F4D31EDFBABC5E0EFCC38318

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Please make sure to refer to these and / or the relevant agreement which you have with Newton Waterproofing Systems.