

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

Revision: 1.5 - 16th October 2023
Code: 309M

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

- Product form Mixture
- Trade name HydroTank 309 Flexible Adhesive

1.2 Relevant identified uses

- Relevant identified uses
- Main use category Professional use
- Uses advised against No additional information available

1.3 Details of the supplier

- Company Address Newton Waterproofing Systems, Newton House, 17-19 Sovereign Way, Tonbridge, Kent TN9 1RH
- Web www.newtonwaterproofing.co.uk
- Email address of the competent person
info@newtonwaterproofing.co.uk
- Emergency telephone number +44 (0)1732 360 095
9am - 5pm (GMT) Mon - Fri

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Contains trimethoxyvinylsilane. May produce an allergic reaction. EUH208

Safety data sheet available on request. EUH210

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. EUH211

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements EUH208 - Contains trimethoxyvinylsilane. May produce an allergic reaction.
EUH210 - Safety data sheet available on request.
EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.2 Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

Mixture does not contain substance (s) classified as PBT or vPvB in concentrations above 0,1%.

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
dioctyltin dilaurate (3648-18-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
trimethoxyvinylsilane (2768-02-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
dioctyltin dilaurate(3648-18-8)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Titanium dioxide (Note W)(Note 10)	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2 REACH-no: 01-2119489379-17	$\geq 0 - < 2,5$	Carc. 2, H351
3-(trimethoxysilyl)propylamine	CAS-No.: 13822-56-5 EC-No.: 237-511-5 REACH-no: 01-2119510159-45	$\geq 0,5 - < 2,5$	Skin Irrit. 2, H315 Eye Dam. 1, H318
trimethoxyvinylsilane	CAS-No.: 2768-02-7 EC-No.: 220-449-8 EC Index-No.: 014-049-00-0 REACH-no: 01-2119513215-52	$\geq 0,5 - < 1$	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapour), H332 (ATE=16,8 mg/l/4h) Skin Sens. 1B, H317

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dioctyltin dilaurate substance listed as REACH Candidate (Dioctyltin dilaurate, stannane, dioctyl-, bis(coco acyloxy) derivs., and any other stannane, dioctyl-, bis(fatty acyloxy) derivs. wherein C12 is the predominant carbon number of the fatty acyloxy moiety)	CAS-No.: 3648-18-8 EC-No.: 222-883-3 EC Index-No.: 050-031-00-9 REACH-no: 01-2119979527-19	≥ 0,1 – < 0,3	Repr. 1B, H360D STOT RE 1, H372

Specific concentration limits:

Name	Product identifier	Specific concentration limits
3-(trimethoxysilyl)propylamine	CAS-No.: 13822-56-5 EC-No.: 237-511-5 REACH-no: 01-2119510159-45	(2,5 ≤ C < 100) Eye Irrit. 2, H319

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

Full text of H- and EUH-statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Move to fresh air. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash with plenty of water/.... Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	Wash with plenty of water/.... If eye irritation persists: Get medical advice/attention. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	May cause slight irritation.
Symptoms/effects after ingestion	Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media All extinguishing media allowed. Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard Not flammable.

5.3. Advice for firefighters

Firefighting instructions Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting Wear suitable protective clothing, gloves and eye/face protection. Wear respiratory protection. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General measures Equip cleanup crew with proper protection. Wear respiratory protection.

6.1.1. For non-emergency personnel

Emergency procedures Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment Equip cleanup crew with proper protection.
Emergency procedures Ventilate area.

6.2. Environmental precautions

Do not dispose of waste into sewer. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up On land, sweep or shovel into suitable containers. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". Concerning disposal elimination after cleaning, see section 13. See Section 8. Exposure controls and personal protection.

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Precautions for safe handling

Avoid any direct contact with the product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Store in dry, well-ventilated area. Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.

Incompatible products

Strong bases. Strong acids.

Incompatible materials

Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

Adhesives, sealants.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Titanium dioxide (13463-67-7)	
Ireland - Occupational Exposure Limits	
OEL STEL	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust

8.1.2. Recommended monitoring procedures No additional information available

8.1.3. Air contaminants formed No additional information available

8.1.4. DNEL and PNEC No additional information available

8.1.5. Control banding No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure.

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

8.2.2. Personal protection equipment

Personal protective equipment: Gloves. Safety glasses. Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection: Safety glasses. Chemical goggles or safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	With side shields	EN 166

8.2.2.2. Skin protection

Skin and body protection: No special clothing/skin protection equipment is recommended under normal conditions of use

Hand protection Time of penetration is to be checked with the glove producer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear. Wear protective gloves.

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	3 (> 60 minutes)	> 0,35		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection: No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Consumer exposure controls: Avoid contact with skin and eyes. Wash hands and other exposed areas with soap and water before leaving work.

Other information: Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke during use.

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Colour	According to product specification.
Appearance	Pasty liquid.
Odour	Characteristic.
Odour threshold	Not available
Melting point	Does not apply
Freezing point	Not applicable
Softening point	Not applicable
Boiling point	Not applicable.
Flammability	Non flammable.
Explosive properties	Product is not explosive.
Oxidising properties	Non oxidizing material according to EC criteria.
Explosive limits	Not available
Lower explosion limit	Not applicable.
Upper explosion limit	Not applicable
Flash point	> 100 °C (ISO 3679)
Auto-ignition temperature	≥ 235 °C (calculated value)
Decomposition temperature	Not applicable
pH	Insoluble in water
Viscosity, kinematic	6200 mm ² /s
Viscosity, dynamic	9920 mPa·s (Brookfield spindle 96, 1 rpm)
Non-Newtonian liquid	Thixotropic behaviour
Solubility	Water: Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not applicable for preparations
Partition coefficient n-octanol/water (Log Pow)	Not applicable for preparations
Vapour pressure	Not applicable.
Vapour pressure at 50°C	Not applicable
Density	1,6 g/cm ³
Relative density	1,6
Relative vapour density at 20°C	Not available
Particle characteristics	Not applicable

3-(trimethoxysilyl)propylamine	
Boiling point	190 °C
Flash point	90 °C
Titanium dioxide	
Boiling point	3000 (2500 – 3000) °C
dioctyltin dilaurate	
Boiling point	> 180 °C Decomposes before boiling
Flash point	198 °C
Vapour pressure	0,000015 hPa
trimethoxyvinylsilane	
Boiling point	123 °C
Flash point	24,5 °C
Vapour pressure	11,9 hPa

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content: 16 g/l

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Additional hazards when processed. release of (highly) toxic gases/vapours. Methanol. fume. Carbon monoxide. Carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)

Not classified

Acute toxicity (dermal)

Not classified

Acute toxicity (inhalation)

Not classified

3-(trimethoxysilyl)propylamine (13822-56-5)	
LD50 oral rat	5628 mg/kg
LD50 dermal rabbit	15800 mg/kg
LC50 Inhalation - Rat	476 mg/l/4h

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LD50 dermal rat	> 10000 mg/kg
LD50 dermal rabbit	> 10000 mg/kg

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

Titanium dioxide (13463-67-7)	
LC50 Inhalation - Rat	> 6,82 mg/l
LC50 Inhalation - Rat (Dust/Mist)	> 6,82 mg/l/4h

dioctyltin dilaurate (3648-18-8)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg

trimethoxyvinylsilane (2768-02-7)	
LD50 oral rat	7236 mg/kg
LD50 dermal rabbit	3880 mg/kg
LC50 Inhalation - Rat [ppm]	2773 ppm/4h
LC50 Inhalation - Rat (Vapours)	16,8 mg/l/4h

Skin corrosion/irritation Not classified
pH: insoluble in water

Additional information Based on available data, the classification criteria are not met

Titanium dioxide (13463-67-7)	
pH	7

Serious eye damage/irritation Not classified
pH: insoluble in water

Additional information Based on available data, the classification criteria are not met

Titanium dioxide (13463-67-7)	
pH	7

Respiratory or skin sensitisation Not classified

Additional information Based on available data, the classification criteria are not met

Germ cell mutagenicity Not classified

Additional information Based on available data, the classification criteria are not met

Carcinogenicity Not classified

Additional information Based on available data, the classification criteria are not met

Reproductive toxicity Not classified

Additional information Based on available data, the classification criteria are not met

dioctyltin dilaurate (3648-18-8)	
NOAEL (animal/male, F0/P)	0,3 – 0,4 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (animal/female, F0/P)	0,3 – 0,5 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

STOT-single exposure Not classified

Additional information Based on available data, the classification criteria are not met

STOT-repeated exposure Not classified

Additional information Based on available data, the classification criteria are not met

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

dioctyltin dilaurate (3648-18-8)	
STOT-repeated exposure	Causes damage to organs (immune system) through prolonged or repeated exposure.

trimethoxyvinylsilane (2768-02-7)	
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight/day

Aspiration hazard Not classified

Additional information Based on available data, the classification criteria are not met

Parabond 600	
Viscosity, kinematic	6200 mm ² /s
3-(trimethoxysilyl)propylamine (13822-56-5)	
Viscosity, kinematic	1,7 mm ² /s at 20 °C
dioctyltin dilaurate (3648-18-8)	
Viscosity, kinematic	27,411 mm ² /s
trimethoxyvinylsilane (2768-02-7)	
Viscosity, kinematic	1,031 mm ² /s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

11.2.2. Other information Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) Not classified

Hazardous to the aquatic environment, long-term (chronic) Not classified

Titanium dioxide (13463-67-7)	
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
LC50 - Fish [2]	> 10000 mg/l
EC50 - Crustacea [1]	19,3 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	27,8 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 1000 mg/l
EC50 - Other aquatic organisms [2]	61 mg/l
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	> 100 mg/l pseudokirchneriella subcapitata
NOEC (chronic)	≥ 2,92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic algae	5600 mg/l

dioctyltin dilaurate (3648-18-8)	
LC50 - Fish [1]	> 0,09 mg/l
EC50 - Crustacea [1]	> 0,21 mg/l
EC50 72h - Algae [1]	> 0,0018 mg/l

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

trimethoxyvinylsilane (2768-02-7)	
LC50 - Fish [1]	191 mg/l
EC50 - Crustacea [1]	167 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	> 957 mg/l
ErC50 algae	> 100 mg/l (OECD 201 method)
NOEC chronic crustacea	28,1 mg/l
EC chronic algae	25 mg/l

12.2. Persistence and degradability

Parabond 600	
Persistence and degradability	Not established.
Titanium dioxide (13463-67-7)	
Persistence and degradability	Not readily biodegradable.
trimethoxyvinylsilane (2768-02-7)	
Biodegradation	51 %

12.3. Bioaccumulative potential

Parabond 600	
Partition coefficient n-octanol/water (Log Pow)	Not applicable for preparations
Partition coefficient n-octanol/water (Log Kow)	Not applicable for preparations
Bioaccumulative potential	Not established.
3-(trimethoxysilyl)propylamine (13822-56-5)	
Partition coefficient n-octanol/water (Log Pow)	0,2
Bioaccumulative potential	Low bioaccumulation potential.
Titanium dioxide (13463-67-7)	
BCF - Fish [1]	352
dioctyltin dilaurate (3648-18-8)	
Partition coefficient n-octanol/water (Log Pow)	9,26

12.4. Mobility in soil

dioctyltin dilaurate (3648-18-8)	
Surface tension	33,96 mN/m

12.5. Results of PBT and vPvB assessment

Parabond 600	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
Mixture does not contain substance (s) classified as PBT or vPvB in concentrations above 0,1%.	

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information

Avoid release to the environment.

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product/Packaging disposal recommendations Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport Not applicable

Transport by sea Not applicable

Air transport Not applicable

Inland waterway transport Not applicable

Rail transport Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)	Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)
REACH Annex XIV (Authorisation List)	Contains no substance(s) listed on REACH Annex XIV (Authorisation List)
REACH Candidate List (SVHC)	Contains substance(s) listed on the REACH Candidate List in concentrations $\geq 0.1\%$ or SCL: Dioctyltin dilaurate, stannane, dioctyl-, bis(coco acyloxy) derivs., and any other stannane, dioctyl-, bis(fatty acyloxy) derivs. wherein C12 is the predominant carbon number of the fatty acyloxy moiety (EC 222-883-3, CAS 3648-18-8)
PIC Regulation (Prior Informed Consent)	Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals): dioctyltin dilaurate (3648-18-8)
POP Regulation (Persistent Organic Pollutants)	Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)
Ozone Regulation (1005/2009)	Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)
VOC Directive (2004/42)	VOC content: 16 g/l
Explosives Precursors Regulation (2019/1148)	Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)
Drug Precursors Regulation (273/2004)	Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

SECTION 16: OTHER INFORMATION

Indication of changes:

Regulatory information.

Abbreviations and acronyms:

CAS-No.	Chemical Abstract Service number
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
BCF	Bioconcentration factor
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
LOAEL	Lowest Observed Adverse Effect Level
LD50	Median lethal dose
LC50	Median lethal concentration
IOELV	Indicative Occupational Exposure Limit Value
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PBT	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
vPvB	Very Persistent and Very Bioaccumulative
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
ATE	Acute Toxicity Estimate
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
SDS	Safety Data Sheet

Data sources

ECHA (European Chemicals Agency). For more information regarding the use of this product, please refer to our technical information or contact the sales department in your region. Supplier's safety documents. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Training advice

Normal use of this product shall imply use in accordance with the instructions on the packaging.

Other information:

None.

HydroTank 309 Flexible Adhesive

Flexible Adhesive Mastic

Full text of H- and EUH-statements:	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
Repr. 1B	Reproductive toxicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
EUH208	EUH208	Calculation method
EUH210	EUH210	Calculation method
EUH211	EUH211	On basis of test data

SDS EU DL Chemicals

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Any specification/advice provided is only valid if used with products supplied by John Newton and Company Ltd (trading as Newton Waterproofing Systems). Newton Waterproofing Systems reserve the right to update product literature at any time. Please always refer to our [website](#) for the latest versions.