

System 400

NEWTON 410 GEODRAIN

Externally Applied Drainage Membrane

Rev 3.0 - 20 March 2018

PRODUCT CODE - M18



EN 13252:2016

DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) No. 305/2011

1. Unique Identification Code of the Product Type:

M18

2. Intended Use/s:

Geocomposite for applications in the drainage sector **S + F + D**

3. Manufacturer:

Newton Waterproofing Systems
 (a trading name of John Newton & Company Ltd.)
 Newton House
 17-20 Sovereign Way
 Tonbridge
 Kent
 TN9 1RH
 01732 360095
www.newtonwaterproofing.co.uk

4. Authorised Representative:

Not Applicable

5. System/s of AVCP:

System 2+

6a. Harmonised Standard:

EN 13252:2016

NOTIFIED BODY/IES:

SKZ Testing GmbH, NB: 1213

6b. European Assessment Document:

Not applicable

NEWTON 410 GEODRAIN

Externally Applied Drainage Membrane

EUROPEAN TECHNICAL ASSESSMENT:

Not applicable

TECHNICAL ASSESSMENT BODY:

Not applicable

NOTIFIED BODY/IES:

Not applicable

7. Declared Performance:

	Essential characteristics	Declared performance		Test standard	Harmonised Technical Standard
		Mean value	Tolerance		
Geotextile (textile layer)	Tensile strength - MD	9.0 kN/m	- 1.2 kN/m	EN 10319	EN 13252:2016
	Tensile strength - CDM	9.0 kN/m	- 1.2 kN/m		
	Dynamic perforation	29 mm	+ 5.8 mm	EN 13433	
	Puncture	1,250 kN	- 0.125 kN	EN 12236	
	Opening size	120 µm	± 36 µm	EN 12956	
	Permeability	50 x 10 ⁻³ m/s	- 15 x 10 ⁻³ m/s	EN 11058	
	Durability	To be covered within 2 weeks after installation. Durable for at least 100 years in each natural soil (ph-value between 4 and 9; ground temperature ≤ 25°C)			
Geomembrane (membrane + textile)	Permeability - MD	3.3 l/ms	± 0.5 l/ms	EN 12958	
	Permeability - CMD	3.4 l/ms	± 0.5 l/ms		
	Tensile strength - MD	15 kN/m	± 1 kN/m	EN 10319	
	Tensile strength - CMD	15 kN/m	± 1 kN/m		
		Durability	To be covered within 2 weeks after installation. Durable for at least 5 years in each natural soil (ph-value between 4 and 9; ground temperature ≤ 25°C)		
	Hazardous substances	Less than limited by national regulations.		National regulations valid in the EU member states	

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Warren Muschialli - Managing Director



At: Newton Waterproofing Systems
Newton House
17-20 Sovereign Way
Tonbridge
Kent
TN9 1RH

On: 12 February 2014



NEWTON 410 GEODRAIN

Externally Applied Drainage Membrane

				Newton Waterproofing Systems Newton House 17-20 Sovereign Way Tonbridge Kent TN9 1RH		M18 EN 13252:2016 1213 Geocomposite for applications in the drainage sector S + F + D	
	Essential Characteristics	Declared Performance		Test Standard	Harmonised Technical Standard		
		Mean value	Tolerance				
Geotextile (textile layer)	Tensile strength - MD	9.0 kN/m	- 1.2 kN/m	EN 10319	EN 13252:2016		
	Tensile strength - CDM	9.0 kN/m	- 1.2 kN/m				
	Dynamic perforation	29 mm	+ 5.8 mm	EN 13433			
	Puncture	1,250 kN	- 0.125 kN	EN 12236			
	Opening size	120 µm	± 36 µm	EN 12956			
	Permeability	50 x 10 ⁻³ m/s	- 15 x 10 ⁻³ m/s	EN 11058			
	Durability	To be covered within 2 weeks after installation. Durable for at least 100 years in each natural soil (ph-value between 4 and 9; ground temperature ≤ 25°C)					
Geocomposite (membrane + textile)	Permeability - MD	3.3 l/ms	± 0.5 l/ms	EN 12958			
	Permeability - CMD	3.4 l/ms	± 0.5 l/ms				
	Tensile strength - MD	15 kN/m	± 1 kN/m	EN 10319			
	Tensile strength - CMD	15 kN/m	± 1 kN/m				
Durability	To be covered within 2 weeks after installation. Durable for at least 5 years in each natural soil (ph-value between 4 and 9; ground temperature ≤ 25°C)						
Hazardous substances	Less than limited by national regulations.			National regulations valid in the EU member states.			

Newton Waterproofing Systems reserve the right to update product literature at any time. Please always refer to our [website](#) for the latest versions.