

Product Registration Certificate

Printed on: 22 Aug 2012

Registration No. 1866
Title PC Leakinject Uni 6816E
Status Authorised For Use
Supersedes ProductID N/A
Superseded By ProductID N/A
Date Authorised for Use 22 Aug 2012
Primary Use A rigid, water sealing injection resin for sealing cracks and voids in concrete constructions which are not liable to setting and movement.
Additional Info/KeyWords Tradecc nv, Terbekehofdreef 50-52, BE-2610, Antwerp, Belgium. Tel: 03828 94 95 info@tradec.be This product is a low viscosity polyurethane resin which reacts with water to form a rigid hydrophobic seal. It is fast reacting and stops active water leaks with a high flow and/or hydrostatic pressure. Free expansion is in the range 1700-2200%.

Classification Hierarchy Civil
 Bridges and Structures

Manufactured By Tradecc

Requirements

ReqID	Requirement	Status	Trial
No records to display.			

Conditions

Description	Linked To ReqID
Use according to the manufacturer's instructions	
Prior to use, an assessment should be carried out according to the COSHH (Control of Substances Hazardous to Health) regulations.	
Prior to use in a below ground location, a concession against the requirements of LU Standard 1-085 'Fire Safety Performance of Materials' is required.	

Evidence

EvidenceText	EvidenceType	FileName	Linked To ReqID
Technical Data	User Guide	PC Leakinject Uni 6816 E TD.pdf	
Health and Safety Data - Catalyst	Safety Data / Information	PC 6816 E CAT EN.pdf	
Health and Safety Data - Base Resin	Safety Data / Information	PC 6816 E EN.pdf	
Injection Resin Summary	User Guide	Injection resins summary.pdf	

Refer to Web site www.lu-apr.co.uk to check current status, download attachments and for details of other products.

MAYOR OF LONDON