

System 400

NEWTON 402 CCS-M

Type A - Externally Applied Waterproofing Membrane

Rev 1.0 - 23 April 2021

PRODUCT CODE: 402



EN 13967:2012

DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) No. 305/2011

1. Unique Identification Codes of the Product Type:

402

2. Intended Use/s:

Flexible sheets for waterproofing - Plastic and rubber damp proof sheets including plastic and rubber basement tanking sheets

3. Manufacturer:

Newton Waterproofing Systems
 (a trading name of John Newton & Company Ltd.)
 Newton House
 17-20 Sovereign Way
 Tonbridge
 Kent
 TN9 1RH
 01732 360095
www.newtonwaterproofing.co.uk

4. Authorised Representative:

Not Applicable

5. System/s of AVCP:

System 2+

6a. Harmonised Standard:

EN 13967:2012

NOTIFIED BODY:

MPA Braunschweig, NB: 0761

NEWTON 402 CCS-M

Type A - Externally Applied Waterproofing Membrane

6b. European Assessment Document:

Not applicable

EUROPEAN TECHNICAL ASSESSMENT:

Not applicable

TECHNICAL ASSESSMENT BODY:

Not applicable

NOTIFIED BODY/IES:

Not applicable

7. Declared Performance:

Essential characteristics to BS EN 13967:2012	Test Standard & Conditions	Result	Unit of measure
Water tightness	BS EN 1928 Method A Water pressure: 2 bar Test period: 24 hrs	Watertight	
Resistance to tearing (nail shank)	BS EN 12310-1 Lengthwise Across	518 ±8.31 470 ±14.8	N N
Joint strength (glued seam)	BS EN 12317-2 Glued seam	100	N/50mm
Tensile properties	BS EN 12311-2 Lengthwise Across	250 200	N/50mm N/50mm
Reaction to fire	13501-1:2019-05	Euroclass E	

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Warren Muschialli - Managing Director

At: Newton Waterproofing Systems
Newton House
17-20 Sovereign Way
Tonbridge
Kent
TN9 1RH



On: 23 April 2021

NEWTON 402 CCS-M

Type A - Externally Applied Waterproofing Membrane



Newton Waterproofing
Systems
Newton House
17-20 Sovereign Way
Tonbridge
Kent TN9 1RH

402
BS EN 13967:2012
0761
Flexible sheets for waterproofing.
Plastic and rubber damp proof
sheets including plastic and
rubber basement tanking sheets

Essential characteristics to BS EN 13967:2012	Test Standard & Conditions	Result	Unit of measure
Water tightness	BS EN 1928 Method A Water pressure: 2 bar Test period: 24 hrs	Watertight	
Resistance to tearing (nail shank)	BS EN 12310-1 Lengthwise Across	518 ±8.31 470 ±14.8	N N
Joint strength (glued seam)	BS EN 12317-2 Glued seam	100	N/50mm
Tensile properties	BS EN 12311-2 Lengthwise Across	250 200	N/50mm N/50mm
Reaction to fire	13501-1:2019-05	Euroclass E	