



DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) No. 305/2011

1. UNIQUE IDENTIFICATION CODES OF THE PRODUCT TYPE:

401GM

2. INTENDED USE/S:

Flexible sheets for waterproofing - Plastic and rubber damp proof sheets including plastic and rubber basement tanking sheets

3. MANUFACTURER:

Newton Waterproofing Systems
(a trading name of John Newton & Company Ltd.)
Newton House
17-20 Sovereign Way
Tonbridge
Kent
TN9 1RH
01732 360095
www.newtonwaterproofing.co.uk

4. AUTHORISED REPRESENTATIVE:

Not Applicable

5. SYSTEM/S OF AVCP:

System 2+

6A. HARMONISED STANDARD:

EN 13967:2012

NOTIFIED BODY:

SKZ Testing GmbH, NB: 1213

6B. EUROPEAN ASSESSMENT DOCUMENT:

Not applicable

EUROPEAN TECHNICAL ASSESSMENT:

Not applicable

TECHNICAL ASSESSMENT BODY:

Not applicable

NOTIFIED BODY/IES:

Not applicable

7. DECLARED PERFORMANCE:

Essential characteristics to BS EN 13967:2012	Test Standard & Conditions	Result	Unit of measure
Water tightness	BS EN 1928 Method A Water pressure: 2 bar Test period: 24 hrs	Watertight	
Durability	EN 1847 Method A Watertightness after artificial ageing Watertightness after exposure to chemicals	Watertight	
Dangerous substances		NPD	
Reaction to fire	13501-1:2019-05	Euroclass F	

8. APPROPRIATE TECHNICAL DOCUMENTATION AND/OR SPECIFIC TECHNICAL DOCUMENTATION:

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Warren Muschialli - Managing Director



At: Newton Waterproofing Systems
Newton House
17-20 Sovereign Way
Tonbridge
Kent
TN9 1RH

On: 12 July 2021



HydroBond SAGM[®]

Type A - Self-Adhesive Gas & Waterproofing Membrane

		<p>Newton Waterproofing Systems Newton House 17-20 Sovereign Way Tonbridge Kent TN9 1RH</p>	<p>401GM BS EN 13967:2012 1213 Flexible sheets for waterproofing. Plastic and rubber damp proof sheets including plastic and rubber basement tanking sheets</p>	
Essential characteristics to BS EN 13967:2012	Test Standard & Conditions		Result	Unit of measure
Water tightness	BS EN 1928 Method A Water pressure: 2 bar Test period: 24 hrs		Watertight	
Durability	EN 1847 Method A Watertightness after artificial ageing Watertightness after exposure to chemicals		Watertight	
Dangerous substances			NPD	
Reaction to fire	13501-1:2019-05		Euroclass F	

Newton Waterproofing Systems reserve the right to update product literature at any time. Please always refer to our [website](#) for the latest versions.