Ground & Surface Water Pump



Rev 1.0 - 12th December 2023 Code - TAS250

Identification of the Substance/Mixture and of the Company/Undertaking

Shell Ondina Oil 32,67 Material name Recommended use White mineral oil. SDS Code 493411 Identified uses Lubricating oil for the mechanical seals of the Newton TAS250 Pump **Company Address** Newton Waterproofing Systems, Newton House, 17-19 Sovereign Way, Tonbridge, Kent TN9 1RH www.newtonwaterproofing.co.uk Web . Email address of the competent person . info@newtonwaterproofing.co.uk Emergency telephone number +44 (0)1732 360 095 9am - 5pm (GMT) Mon - Fri

Hazards Identification

٠	GHS Classification	Not hazardous
G	HS Label Elements Symbol(s)	
٠	Signal Words	No signal word
٠	Hazard Statement	Not classified under GHS criteria.
GHS Precautionary Statements		
٠	Prevention	No precautionary phrases.
٠	Response	No precautionary phrases.
٠	Storage	No precautionary phrases.
٠	Disposal	No precautionary phrases.
۰	Other Hazards not result in classification	Not classified as flammable but will burn. See Section 4 - 8 before use for Prevention/Response/Storage/Disposal. Used oil may contain harmful impurities.

Composition/Information on Ingredients

٠	Substance or Mixture	Substance (UVCB)
٠	Chemical Description	White mineral oil.
٠	Component Information	Lubricant base oil (White mineral oil) 100%
٠	Chemical Formula	Not possible to define.
٠	CAS registry number	Trade secret
٠	Additional Information	If product contained highly refined mineral oil, it contains <3% DMSO- extract, according to IP346.
٠	Pollutant Release and Transfer Register (PRTR) Law	Not applicable
٠	Industrial Safety and Health Law	Not applicable
•	Poisonous and Deleterious	Not applicable

Ground & Surface Water Pump

Substance Control Law

Classification of components according to GHS

[Chemical Identity/Hazard Class (category)/Hazard Statement/Conc.] Data not available.

First Aid Measures

- General Information
- Not expected to be a health hazard when used under normal conditions. Inhalation Remove person to fresh air and keep at rest in a position comfortable for breathing. Cover with blanket to keep warm and rest in a quiet surrounding. Seek immediate medical advice and attention. Skin Contact Wash skin with large amount of water using soap. Eye Contact Rinse cautiously with clean water for several minutes. Remove contact lenses, if present and easy to do, and continue rinsing. After rinsing for a minimum of 15 minutes, seek medical advice and attention. Ingestion Without inducing vomiting, call a doctor for treatment. If mouth has been dirtied, clean with water. Most Important Symptoms/Effects, If swallowed, may irritate mucous membrane of stomach and induce vomiting. Acute & Delayed Inhalation if mist may cause feeling ill. Skin contact and eye contact may cause irritation. Immediate Medical Attention, Treat symptomatically. Call a doctor or poison control center for guidance.

Firefighting Measures

Special Treatment

Clear fire area of all non-emergency personnel

	0 , .	
•	Suitable Extinguishing Media	Concentrated strong liquid in mist and powder forms, carbon dioxide and foam. Use powder and carbon dioxide may be used small fires only. Effective to use foam to shutdown the air in a large fires.
•	Unsuitable Extinguishing Media	Do not use water in a jet.
•	Specific Hazards Arising from Chemicals	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds
•	Fire Fighting Instructions	Water the surrounding equipment to cool them down. Cordon off the affected place and its vicinity to all, except the concerned parties.
•	Protective Equipment & Precautions for Fighters	Ensure to wear protective equipment and approach from windward.

Accidental Release Measures

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Section 8 of this Material Safety Data Sheet. See Section 13 for information on disposal. Observe the relevant local and international regulations.

- **Personal Precautions** Avoid contact with skin and eyes. Prepare suitable equipment and materials. Protective Equipment and **Emergency Procedures**
- **Environmental Precautions**

Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. In event of entering in the sea, extend oil fences to prevent from spreading, and sop up with absorbent materials. Use chemicals and/or detergents, they must satisfy technical standards as set by the Ministry of Land, Infrastructure and Transport / Ministry of the Environment.

Ground & Surface Water Pump

•	Methods and Material for Containment and Clean-Up	Promptly remove all ignition sources and stop leakages. In a small leakage, absorb and recover by use of soil, sand, sawdust and waste clothes. In a large leakage, cordon off the danger zone, prevent from entering and enclose it with sand bank and stop outflow. Cover liquid surface with foam, and recover liquid into containers.
•	Additional Advice	Local authorities should be advised if significant spillages cannot be contained.
Handling and Storage		
•	Technical Measures	In handling this material over the allocated volume, ensure approval to meet requires of the laws. Keep away from heat, sparks, open flames, hot objects. No smoking. Take measures against static discharge. Ensure to wear clothing and shoes made of conductive materials. When fixing or processing machine, it carries out after removing dangerous objects completely. NEVER suck up (siphoning) this material by mouth. Wear suitable protective equipment if skin or eye contact may cause. Seal containers hermetically without handling in violent such as falling, dropping, or jolting.
•	Ventilation Precautions	See Section 8
•	Precautions for Safe Handling	Use under normal temperature. Prevent from mixing water and impurity. Avoid contact with halogens, strong acids, alkali and oxidizing materials.
STO	DRAGE	
٠	Conditions for Safe Storage	Keep containers tightly closed and in a cool, well-ventilated place away from direct sunlight. It is recommended to lock up storage area. Use properly labelled and closeable containers. Avoid heat, sparks, open flame and static accumulation.
•	Technical Measures	All electrical appliances shall be explosion-proof types, and they all must be earthed.
•	Precautions for Safe Storage	Avoid contact and storage in same place with halogens, strong acids, alkali and oxidizing materials.
•	Recommended Materials	Store in original containers. Do not pressurize empty containers. May cause rupture. Do not weld, heat up, drill or cut containers. May ignite the residue and cause explosion.

Exposure Controls/Personal Protection

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

•	Equipment	Seal or install ventilations for mist occurs. Install eye shower and body shower near working site.
٠	Standard Concentration Control	Not specified
٠	Occupational Exposure Limits	Japan Society for Occupational Health(2010)(1) 3mg/m3 (as Oil mist, mineral) ACGIH(2010) TWA[Inhalable fraction.](2) 5mg/m3 (as Oil mist, mineral)
•	Protective Equipment	Skin protection not ordinarily required beyond standard issue work clothes.
•	Respiratory Protection	No respiratory protection is ordinarily required under normal conditions of use. Use appropriate equipment in response to the circumstances.
•	Hand Protection	Use oil-proof protective hand gloves under prolonged or repeated skin contact.
•	Eye Protection	Wear safety glasses or full face shield if splashes are likely to occur.
٠	Skin and Body Protection	Use oil-proof/long sleeved clothing under prolonged usage.

© Newton Waterproofing Systems Newton House, 17-19 Sovereign Way Tonbridge, Kent, TN9 1RH

Ground & Surface Water Pump

 Appropriate Sanitary Measures
 Remove immediately all contaminated clothing. Contaminated clothing must be laundered before reuse.

Physical and Chemical Properties

	-	
•	Physical state	Liquid at room temperature.
•	Colour	Colourless. Clear.
•	Odour	Characteristic mineral oil pH : Not applicable.
•	Initial Boiling Point	Expected >250°C
•	Pour Point	<-10°C
•	Flash Point	≥ 200°C (COC)
•	Upper / Lower Flammability Explosion limits	Typical 1 - 7 %(V) (based on mineral oil)
•	Auto-ignition temperature	Data not available. Expected >320°C
•	Density	Approx. 0.86g/cm3 (15°C)
•	Solubility	Water: Negligible. Other solvents: Data not available
•	Decomposition Temperature :	Data not available
•	Vapour pressure	Data not available
•	Vapour density	Data not available. Expected >1
•	n-octanol/water partition coefficien	t (log Pow) Data not available
•	Evaporation rate	Data not available

Stability and Reactivity

- Chemical Stability
- Hazardous Reactivity
- Conditions to Avoid
- Incompatible Materials
- Hazardous Decomposition
 Products

Toxicological Information

- Acute Toxicity
- Skin Corrosion/Irritation
- Serious Eye Damage/Irritation
- Respiratory or Skin Sensitisation
- Germ Cell Mutagenicity
- Carcinogenicity
- Reproductive and Developmental Toxicity

Stable under normal condition.

Avoid contact with strong oxidising agent.

Avoid contact with halogens, strong acids, alkalis, and oxidizing materials.

Data not available.

Hazardous decomposition products are not expected to form during normal storage. Generates smoke, carbon monoxide, sulfurous acid gas etc. during combustion.

- 1 Oral Expected to be of low toxicity: $LD_{50} > 15,000 \text{ mg/kg}$, Rat 2 Dermal Expected to be of low toxicity: $LD_{50} > 5,000 \text{ mg/kg}$, Rat 3 Inhalation (Vapour) Data not available
- 4 Inhalation (Mist) Data not available
- Not classified as a skin irritation (rabbit test).
- Not classified as an eye irritation (rabbit test).
- No data available concerning respiratory sensitisation. Not classified as a skin sensitiser (pig test).
- Data not available.

Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC monographs: Group 3). White mineral oils are the higher degree of refining and not classified as a carcinogen.

Not classified as a Reproductive and Developmental Toxicity (rabbit test, 4,350mg/kg bw/day, 5days a week, 13weeks)

Page 4 of 7

Ground & Surface Water Pump

- Specific target organ toxicity
- Aspiration Hazard

Ecological Information

- Caution
- Acute Aquatic Toxicity
- Chronic Aquatic Toxicity
- Mobility
- Persistence/degradability
- Bioaccumulative Potential

Disposal Considerations

Material Disposal

• Container Disposal

Transport Information

International Restriction

- UN Class
- UN Number
- Other Information
- Domestic Restriction
- Land Fire Service Law
- Container
- Sea
- Air
- Specific safety measures transportation

Not expected to be a hazard.

Not classified as a hydrocarbon with kinetic viscosity \leq 20.5mm2/s measured at 40°C. Not considered an aspiration hazard.

Poorly soluble mixture. May cause physical fouling of aquatic organisms.

Fish Practically non toxic: LC50>10,000mg/L (Lepomis macrochirus, 96hrs)

Not expected to be a hazard.

Generally floats on water. Lubricating oil components have estimated log Koc >3, indicating these components are likely to be adsorbed onto soil and sediment and are not likely to leach to ground water.

Data not available

Data not available

1 - Waste disposal yourself or entrust the industrial waste treatment company who obtained the prefectural governor's permission or municipal corporation. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

2 - Do not dispose into the environment, in drains or in water courses.
3 - For landfill disposal, destroy by fire and confirm cinders agreed to Waste Disposal Law

4 - In event of burning this material, ensure to carryout work in safe place with guards in position, and select a method that would not cause any harm or damage to others during combustion or explosion.

Purify and recycle or performs suitable disposal in accordance with the standard of related laws and regulations. Disposal with remove content completely.

Not applicable.

Not applicable.

This material is not classified as dangerous under IMDG/IATA regulations.

Since domestic laws and regulations shown below are applicable, containers and transportation methods shall be required to follow each and every regulation.

Dangerous goods. Group 4 (flammable liquid), Class 4 petroleum, Danger grade III (water soluble)

If product classified as dangerous goods, use containers (other than tanker, tank car and tank truck) for transportation usage, shall meet the Clause 2, Notice Attachment 3, concerning dangerous materials.

Ship Safety Law: Not Dangerous Goods.

Civil Aeronautics Act: Not Dangerous Goods.

1 - Caution: Flammable.and conditions for

2 - Transport remarkably with containers may not cause friction or agitation 3 - Display signage on vehicle and provide with fire fighting equipment, if and when required to transport more than the specified quantity. Total piled height of vehicle shall be less than 3 meters.

4 - Consolidation of this material with dangerous goods belonging to the 1st and 6th Classification is prohibited.

Ground & Surface Water Pump

5 - Abide by other laws and regulations that are applicable.

Dangerous goods. Group 4 (flammable liquid), Class 4 petroleum, Danger

Regulatory Information

International Information

- EINECS/ELINCS (EC) All components listed or polymer exempt.
- TSCA (USA)
- METI (JAPAN)

Domestic Information

- Fire Service Law
- Marine Pollution Protection Law
- Sewage Control Law
- Water Pollution Prevention Law
- Waste Disposal and Public Cleaning Law

Other Information

- Subscribe "%" in this document means weight percentage.

[Quotation]

1. Recommendation of Occupational Exposure Limits (2010), Japanese Society of Occupational Health

grade III (water soluble)

Waste Oil Regulation.

2. Thresholds limit values for chemical substances and physical agents and biological exposure indices, ACGIH (2010)

All components listed or in compliance.

All components listed or in compliance.

Mineral Oil Disposal Regulation. (5mg/L)

Oil Disposal Regulation. (5mg/L)

Industrial Waste Regulation.

[Reference]

- Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 2nd/3rd revised edition, UNITED NA-TIONS(2007/2009)

- Japanese Standards Association (JSA), JIS Z 7250:2005, JIS Z 7251:2006, JIS Z 7252:2009

- National Institute of Technology and Evaluation (nite) "GHS Information"
- Japan Advanced Information Center of Safety and Health, "Label and SDS information for GHS model"

Ground & Surface Water Pump

Safety Data Sheet (SDS) about hazardous chemical is provided as reference information for safety handling. Refer to this document and perform suitable handling. Nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such

information for its particular use. There is no warranty against intellectual property infringement.

The information contained in this document is based upon data believed to be reliable through our supply chain at the time. So, Showa Shell Sekiyu could not guarantee all about the contents. This document is based on JIS Z7250:2005, and is not a guarantee of safety.

Contents of SDS updated periodically. SDS compliance is required as a rule to all business enterprises engaged in transaction of chemicals (including products containing them) with other businesses. Retailer/ Wholesaler must provide newest SDS to customers.

DISCLAIMER

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Newton Waterproofing Systems shall not be held liable for any damage resulting from contact with or handling of the above product.

Newton Waterproofing Systems reserve the right to update product literature at any time. Please always refer to our website for the latest versions.

www.newtonwaterproofing.co.uk tech@newtonwaterproofing.co.uk +44 (0)1732 360 095 **Opening Hours:** Monday to Thursday 8:00am - 5:30pm Friday 8:00am - 5:00pm