

HydroBond 403

Externally Applied Waterproofing Membrane

Revision: 8.5 - 29th April 2025
Code: HB-2


INTRODUCTION

Newton HydroBond 403[®] is a high performance, self-healing, composite sheet membrane, with exceptional waterproofing capabilities and is an effective radon barrier, meeting the performance requirements of BR211:2023. When fitted above the raft support or to wall formwork, the membrane locking fleece is encapsulated into the newly placed concrete, becoming fully-engaged to prevent water tracking. If the waterproof LDPE layer is punctured, the exposed hydrophilic coating expands, preventing water ingress, effectively sealing small holes that may be accidentally formed during fixing of the reinforcing steel or the placing and compaction of the concrete.

Newton HydroBond 403 is a component of the HydroBond[®] System that also includes post-applied waterproofing membranes, protection and drainage boards that provide a complete waterproof envelope to the structure to achieve Type A (barrier) waterproofing suitable for Grades 1, 2 and 3 as defined by BS 8102:2022. The HydroBond System is suitable for all below-ground and earth-retained structures from domestic basements to the largest civil engineering projects.

The Newton HydroBond System can be used alongside other Newton products and systems to provide a co-ordinated and combined approach to the waterproofing of the whole structure that includes protection against water ingress to the deck, through construction joints, through and around service entries, and to movement joints.

Correctly protected, the Newton HydroBond System will provide, under normal service conditions, a durable waterproof barrier for the life of the building to which it is installed; the expected lifetime of the building itself should be at least 60 years. The Newton HydroBond system is supported by [BDA Agrément Certificate BAB 17-031/04/A](#) and is accepted by the NHBC as a suitable waterproofing system for Type A Waterproofing to Grades 1, 2 & 3 according to BS 8102:2022.



KEY BENEFITS

- Agrément certificated and NHBC accepted waterproofing system
- Effective radon barrier to the performance requirements of BR211:2023.
- Full mechanical bond to concrete prevents water migration between membrane and structure
- Hydrophilic layer provides self-healing of punctures to the membrane
- Very flexible - Resistant to movement and fissures in substrates
- The HydroBond System completely surrounds the structure
- Excellent resistance to the high alkalinity of concrete



TYPICAL APPLICATIONS

As a continuous membrane to permanent raft and wall formwork such as the raft blinding and piled walls of reinforced concrete earth-retained structures.

SUITABLE SUBSTRATE

RAFT OR SLAB

- Concrete blinding
- Compacted type 1 hardcore
- Compacted sand

The following can be placed above the blinding or hardcore prior to the installation of HydroBond 403:

- Void former
- Clay heave board
- Closed-cell flooring grade insulation
- [HydroBond 410 GeoDrain](#)

WALL FORMWORK

- Existing structure
- Secant or contiguous concrete piles
- Metal sheet piles
- Diaphragm walls
- King post wall
- Sufficiently stable ground such as clay or chalk
- Temporary timber shuttering/formwork

HydroBond 403

Externally Applied Waterproofing Membrane

TECHNICAL DATA			
Performance	Result	Units	
Colour	White/Dark Blue		
Material	Composite*	mm	
Width	1.00	m	
Length	20.00	m	
Area	20.00	m ²	
Thickness	1.60	mm	
Density	1.215	g/m ²	
Packaged weight	24.3	kg	
Shelf life	12	Months	
Application temperature	-10 to +40	°C	
Installed Performance	Result	Units	Test Method
Service temperature	-40 to +100	°C	Manufacturer test
Adhesion to concrete	0.4	N/mm ²	
Elongation at break (Machine)	20	%	DIN EN 12311-2
Elongation at break (Traverse)	50	%	DIN EN 12311-2
Tensile strength (Machine)	> 250	N/50 mm	BS EN 12311-2
Tensile strength (Traverse)	> 200	N/50 mm	BS EN 12311-2
Resistance to static loading - 20 kg load	Watertight		BS EN 12730
Resistance to impact – Al plate - 200 mm drop	Watertight		BS EN 12310-1 - Method 1
Resistance to impact – EPS panel - 500 mm drop	Watertight		BS EN 12310-1 - Method 1
Resistance to impact – Al plate - 250 mm drop	N/A		BS EN 12310-1
Resistance to impact – EPS panel - 1750 mm drop	N/A		BS EN 12310-1
Joint strength - Glued seam	> 100	N/50 mm	BS EN 12311-2
Resistance to tearing - Nail shank – MD**	> 150	N	BS EN 12310-1
Resistance to tearing - Nail shank – Across	> 150	N	BS EN 12310-1
Resistance to fire	Euroclass E		BS EN 13501-1
Water vapour diffusion resistance – Sd value	68	m	BS EN 1931 - Method B
Water vapour diffusion resistance – μ value	42500	μ	Calculated from Sd value
Water vapour diffusion resistance	340	MNs/g	Calculated from Sd value
Radon diffusion coefficient	1.79 x 10 ⁻¹²	m ² /s	DIN ISO 11665-10
Water tightness integrity - Lateral migration	500 kPa for 7 days - Watertight		BS EN 1928 – Method A
Water tightness integrity - Lateral migration	500 kPa for 28 days - Watertight		BS EN 1928 – Method A
Resistance against chemicals - 23°C for 12 weeks	Watertight		DIN EN 1847

*Composite of LDPE, self-healing polymer, polypropylene backing. **Machine Direction.

HydroBond 403


Externally Applied Waterproofing Membrane

Installed Performance	Result	Units	Test Method
Resistance against chemicals - 2 kPa for 28 days	Watertight		BS EN 1928 / DIN EN ISO 291-23/50-2
Durability against thermal ageing - 2 kPa for 24 hours	Watertight		DIN EN 1928 / DIN EN ISO 291-23/50-2
Compatibility with Bitumen - 70°C / 28 days	Not tested		BS EN 1548 / BS EN 1928
Compatibility with Bitumen - 2 kPa / 24 hours	Watertight		BS EN 1928 / DIN EN ISO 291-23/50-2
Friction coefficient	0.8-1.2	μ	
Swelling capacity at 20°C - Linear	28	%	BS ISO 1817
Swelling capacity at 20°C - By volume	111	%	BS ISO 1817
Swelling capacity at 5°C - Linear	12	%	BS ISO 1817
Swelling capacity at 5°C - By volume	39	%	BS ISO 1817

HYDROBOND TAPE

Performance	HydroBond Tape	Units
Product code	HBT	
Colour	White/Dark Blue	
Material	Composite	
Width	75	mm
Length	20.00	m
Area	1.5	m ²
Thickness	1.60	mm
Density	1.215	g/m ²
Packaged weight	0.5	kg
Shelf life	12	Months
Application temperature	-10 to +40	°C

TYPICAL DETAIL



HydroBond 403

Externally Applied Waterproofing Membrane

SPECIFICATION

Newton Waterproofing Systems work in partnership with RIBA NBS who publish our products on [NBS Source](#). The platform integrates seamlessly into project workflows, providing all product data from Newton's NBS BIM Objects, NBS Plus Clauses and RIBA Product Selector into one single source of product information.

NBS Source also hosts a large selection of Newton [case studies](#), as well as product [literature and certifications](#).

A wide range of drawings are available [on our website](#).

FULLY BONDED MEMBRANES

Type A (barrier) protection membranes should be designed and installed to try to overcome defects as outlined in BS 8102:2022 Section 4.3.2 'Defects and remedial measures'. The requirements for the specific properties of the Type A barrier membrane are outlined in Section 8 of the British Standard, on 'Type A (barrier) protection', including Table 3 – 'Waterproofing barriers'.

The membrane should be fully bonded to prevent water entering from a defect and tracking between the membrane and the structure; also known as lateral migration of water from a defect as per BS 8102:2022, Figure 9 – 'Effect of bonded or partially bonded barriers'.

This can be tested by BS EN 1928, Method A. The level of full bond and suitability of use is relevant to both the water depth/pressure tested for both lateral migration and watertightness of the membrane and the laps.

TRAINING AND COMPETENCY OF THE USER

Newton HydroBond 403 should be installed by those with an understanding of the requirement to waterproof retained structures and the knowledge and training to use the product as part of a co-ordinated approach to the waterproofing of the structure, which in many cases will require further waterproofing products so as to achieve the required grade as defined by BS 8102:2022.

[Newton Specialist Contractors \(NSBCs\)](#) are trained by Newton Waterproofing Systems in the correct specification and installation of our waterproofing products and will provide the client with a meaningful insurance backed guarantee for the waterproofing system.

LIFE EXPECTANCY

Newton HydroBond 403 will provide, under normal service conditions, a durable waterproof covering for the life of the building to which it is installed. Please note that this is not the guarantee. The waterproofing guarantee is provided by the specialist waterproofing contractor who installs the product. Clauses can be accessed via the technical resources area.

PACKAGING

Newton HydroBond 403 is supplied in rolls of 1.0 m wide x 20.0 m long. Each roll weighs 24.3 kg.

HYDROBOND SYSTEM PRODUCTS

- [HydroBond 403](#) - Waterproofing Membrane
- [HydroBond SA](#) - Post-applied and self-adhesive waterproofing membrane
- [HydroBond SAGM](#) - Post-applied and self-adhesive waterproofing and gas membrane
- [HydroBond 2K Flex](#) - flexible and reinforced bitumen waterproof coating
- HydroBond Tape - Double-sided sealing tape
- [HydroBond 109-LM](#) - Detailing to DPC
- [HydroBond 314 Bentonite Granules](#) - Swelling detailing powder for use where HydroBond 403 terminates to otherwise difficult to detail building elements
- [HydroBond 914-RT](#) - Reinforcement tape for changes in direction and joints within HydroBond 109-LM

ANCILLARY PRODUCTS

- [HydroBond 410 GeoDrain](#) - Drainage membrane to move water around the structure on sloping sites. Can also be used as protection for all externally applied membranes
- [Hydrocoat 104 Super](#) - Crystalline waterproofing powder used for continuation detailing at piles, capping beams, etc
- [Newton Pipe Collar](#) - Fabric reinforcement collar for 110mm diameter pipe
- [HydroBond Protection Board](#) - Bitumen impregnated protection board

LIMITATIONS

- Cannot be post-applied. Where formwork is removed to expose the concrete, use HydroBond SA or HydroBond 2K-Flex and lap to the HydroBond 403 at the raft edge
- Do not apply at temperatures lower than -10°C or higher than +40°C

INSTALLATION MANUAL

The Installation Manual, Safety Data Sheet and Declaration of Performance for HydroBond 403 can be found on [the product page](#) on our website.

HydroBond 403

Externally Applied Waterproofing Membrane

PROTECTION OF THE MEMBRANE

Newton HydroBond 403 is pre-applied to the horizontal raft support and to permanent wall support such as a piled wall or building line and so is not exposed to potential damage to these areas.

Where the RC wall formwork is removed or where a block wall is built from the raft, the removal of the raft edge formwork exposes the HydroBond 403. This should be protected at the same time and with the same method used to protect the post-applied membrane

Please see installation manual for further information.

Protection methods include:

- Newton drainage membrane, Newton 410 GeoDrain (to sloping sites only)
- HydroBond Protection board
- Suitable closed cell insulation board

SPECIALIST TOOLS REQUIRED

No specialist tools needed.

COLOUR

- Locking fleece - White
- Outer face - HydroBond 403 - Dark Blue

STORAGE

Store in dry conditions at temperatures between 5°C and 25°C. Do not expose to freezing conditions. Do not allow to freeze.

HEALTH AND SAFETY

Use appropriate PPE for the environment the system is installed within. Use products only as stated within this Data Sheet and the SDS and Installation Manual.

Newton Waterproofing Systems reserve the right to update product literature at any time. Please always refer to our [website](#) for the latest versions.

Externally Applied Waterproofing Membrane

Page 6 of 7

HydroBond 403

Externally Applied Waterproofing Membrane

5.8 Compatibility with bitumen	BS EN 1548 Storage temperature: 70°C Storage period: 28 days Test climate: EN ISO 291-23/50-2	Watertight	
Water tightness	BS EN 1928 Method A Water pressure: 2 kPa Test period: 24 hrs Test climate: EN ISO 291-23/50-2		
5.9 Resistance to tearing (nail shank)	BS EN 12310-1 Specimen: 100mm x 200mm v = 100 mm/min Nail spacing: 50 mm Test climate: EN ISO 291-23/50-2 • Lengthwise (along roll / direction of manufacture) • Across (across roll)	Tear propagation resistance (arithmetic mean value, with standard deviation)	
		466 ±15.7 518 ±20.8	N N
5.10 Joint strength	BS EN 12317-2 Specimen: 50mm x 360mm v = 100mm/min Free clamping length: 200mm Test climate: EN 291-23/50-2	Shear resistance along glued seam: long edge (arithmetic mean value, with standard deviation)	
		393 ±9.66	N/50mm Shearing in the glued edge
5.11 Water vapour permeability	BS EN 1931 Method B Climate: 23-0/75	d: 1.60 g: 6.22/10 ⁻⁹ s _D : 68	mm kg/(m ² /s) m
5.13 Resistance to static loading	BS EN 12730 Method B Substrate: concrete	Imposed load 20kg: tight	
5.14 Tensile properties	BS EN 12311-2 Method A v = 100 mm/min Free clamping length: 120mm Test climate: EN ISO 291-23/50-2 • Lengthwise (along roll / direction of manufacture) • Across (across roll)	Maximum tensile force (N/50mm) (arithmetic mean value, with standard deviation)	
		598 ±35.8 893 ±16.9	
		Elongation at break (arithmetic mean value, with standard deviation)	
		93.4 ±13.0 104 ±5.26	
5.16 Reaction to fire	BS EN ISO 11925-2 BS EN 13501-1	Class E	