



DECLARATION OF PERFORMANCE

According to Annex III of the Regulation (EU) No. 305/2011

1. UNIQUE IDENTIFICATION CODES OF THE PRODUCT TYPE:

401GM

Colour: Black

Thickness: 1.2mm

2. INTENDED USE/S:

For damp proofing in buildings, including basement tanking.

3. MANUFACTURER:

Newton Waterproofing Systems
(a trading name of John Newton & Company Ltd.)
Newton House
17-19 Sovereign Way
Tonbridge
Kent
TN9 1RH
01732 360095
www.newtonwaterproofing.co.uk

4. AUTHORISED REPRESENTATIVE:

Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2): Not relevant

5. SYSTEM/S OF AVCP:

System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V

System 2+

6A. HARMONISED STANDARD:

In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard EN 13969:2004

Notified body/ies

British Board of Agrément 0836

6B. EUROPEAN ASSESSMENT DOCUMENT:

In case of a declaration of performance concerning a construction product for which a European Technical Assessment was issued

Not relevant

7. DECLARED PERFORMANCE:

Essential characteristics	Performance	Harmonised Technical Specification
Reaction to Fire	E	EN 13969:2004
Water tightness	Pass	
Resistance to Impact	≥500mm	
Resistance to static loading	20Kg	
Water tightness after ageing	Pass	

To view all test results, refer to the Newton HydroBond SA data sheet

Signed for and on behalf of the manufacturer by:

Name: Warren Muschialli - Managing Director

At: Newton Waterproofing Systems
Newton House
17-19 Sovereign Way
Tonbridge
Kent
TN9 1RH

On: 14th January 2026

